

**e-STUDIO™ 5506AC**

**e-STUDIO™ 6506AC**

**e-STUDIO™ 7506AC**

- > Color Multifunction Printer
- > Up to 75 PPM
- > Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready




# e-STUDIO™ 5506AC/6506AC/7506AC

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
<b>Display</b>	9" Color WVGA Touch Screen Tilting Display
<b>Copy Speed</b>	Color: 55/65/75 PPM (LT), Monochrome: 65/75/85 PPM (LT)
<b>First Copy Out</b>	Color: 6.4/6.4/5.4, Monochrome: 5.2/4.5/4.1
<b>Warm-Up Time</b>	Approx. 20 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
<b>Multiple Copying</b>	Up to 9,999 Copies
<b>Paper Capacity</b>	4-Drawer: 2,280 Sheets/Max. 4,780 Sheets Tandem Drawer: Standard 3,520 Sheets/Max. 6,020 Sheets
<b>Original Feed</b>	Standard 300-Sheet DSDf
<b>Scan Speed &amp; Weights</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Index, Duplex: 9.3-110 lb Index
<b>Max. Original Size</b>	LD
<b>Paper Feed Sizes</b>	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF 1,160 x 2 LT-Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner 2,500-Sheet Ext. LCF LT-Only
<b>Paper Weights</b>	4-Drawer: Standard 540 Sheets x 4-16 lb Bond-140 lb Index Tandem LCF 1,160 Sheets x 2-16 lb Bond-140 lb Index Plus 540 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 120 Sheets-16 lb Bond-110 lb Cover Opt. 2,500-Sheet Ext. LCF LT-Only -16 lb Bond-140 lb Index Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
<b>Duplex</b>	Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
<b>Reproduction Ratio</b>	25% to 400%
<b>Max Duty Cycle</b>	Max. 480K/540K/600K Month (Color: 100%)
<b>Weight</b>	Approx. 470 lb
<b>Approx. Dimensions</b>	37.6" (W) x 28.9" (D) x 48.3" (H)
<b>Toner Yield</b>	39,200, K: 106,600 @ 5%
<b>Power Source</b>	120 Volts, 50/60 Hz, 16 Amps
<b>Power Consumption</b>	Maximum 2.0kW (120V)
<b>CPU</b>	Intel Atom™ 1.75 GHz (Dual-Core)
<b>Memory</b>	4GB
<b>Hard Disk Drive</b>	320GB Self-Encrypting Drive FIPS 140-2 Validated

## e-BRIDGE Next Print Specifications

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Speed</b>	Color: 55/65/75 PPM (LT), Monochrome: 65/75/85 PPM (LT)
<b>Print Resolution</b>	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 x 1,200 dpi (BW/with Smoothing) PS3 Only
<b>Operating Systems</b>	Windows® Vista, Windows Server® 2008/R2, Windows® 7, 8, 8.1, 10, Windows Server® 2012/R2, Macintosh® (Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk® for Macintosh Environments
<b>Printing Protocols</b>	SMB, LPR/LPD, IPP (Ver.1.1) w/Authentication, AppleTalk PAP or EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
<b>Print Drivers</b>	Windows® Vista SP2 (32-bit, 64-bit), Windows Server® 2008 SP2 (32-bit, 64-bit), Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8/8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows® 10 (32-bit, 64-bit), Mac OS® X 10.6.8, 10.7.4, 10.8, 10.9, 10.10, 10.11
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Wireless Device</b>	AirPrint™, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
<b>Device Management</b>	TopAccess, EFMS 6.2 (e-BRIDGE Fleet Management Software)
<b>Account Control</b>	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



## Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408 EAL3+), IEEE2600.1, IEEE802.1X, Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp  
\*Compliant with IEEE2600.1 in High Security Mode.

## Environmental Stds. Certification

Energy Star (V2.0), EPEAT Gold, RoHS  
WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

## Scan Specifications

<b>Scan Speed</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) Standard: Full Color, Auto Color, Monochrome, Grayscale
<b>Scan Modes</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>Scan Resolution</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>File Formats</b>	Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>Image Compression</b>	Color/Grayscale: JPEG (High, Middle, Low)

## Facsimile Specifications

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-Filing Specifications

<b>Operation Method</b>	Color Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## Accessories (Options)

<b>Additional Paper Options</b>	MP2502	Embedded OCR Enabler Single License Five Licenses	GS1080 GS1085
<b>Finishing Options</b>	MJ1111 MJ1112 MJ6106 KA6551 KN1103	Multi-Station Print Enabler Single License Five Licenses Advanced Scanning (ReRite) SharePoint Connector Exchange Connector Google Drive Connector	GS1090 GS1095 GB1280V8 GB1440 GB1450 GB1540
<b>Connectivity/Security Options</b>	GD1370 GN4020 GP1190A GR9000 GR1250 GR1260 GR1290 GS1010 GP1080 GS1007	FAX Unit/2nd Line for FAX Unit Wireless LAN/Bluetooth Hardcopy Security Printing Bluetooth Keyboard Accessory Tray Panel 10-Key Option Card Reader Holder Meta Scan Enabler IPsec Enabler Unicode Font Enabler	Miscellaneous Options Accessible Arm Harness Kit for Coin Controller KK2560 GQ1280

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint and the AirPrint logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1.

## Corporate Office

9740 Irvine Blvd., Irvine, CA 92618  
Tel: 949-462-6000

## East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700

## Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000

## South

2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385

## West Coast

9740 Irvine Blvd., Irvine, CA 92618  
Tel: 949-462-6000

## Web Site

www.business.toshiba.com